# ATF DEXRON II



LIVO ATF Dexron II is high graded automatic transmission fluid formulated with refined base stocks and premium additives to offer maximum performance in vehicles equipped with transmission and hydraulic systems where ATF DEXRON II is recommended.

#### **PRODUCT FEATURES**

- \* Excellent Friction modifiers ensure smooth shifts in different driving conditions.
- \* Very high Viscosity Index ensures appropriate lubrication in both high operating and low starting temperature.
- \* Low pour Point permits fluidity at extremely low temperature.
- \* Excellent thermo-oxidative stability minimizes sludge deposits.
- \* Anti-corrosion, anti-wear, anti-rust and anti-foaming properties.
- \* Outstanding seal compatibility.

### **APPLICATION**

LIVO ATF DEXRON II is designed for use in automatic and semi-automatic transmissions, torque converters of passenger cars and light industrial vehicles, power steering, manual gear boxes and hydraulic systems where ATF DEXRON II is recommended.

## **TECHNICAL SPECIFICATION**

| Characteristics         | Units             | ATF<br>DEXRON II |
|-------------------------|-------------------|------------------|
| Color                   | -                 | Red              |
| Specific Gravity @ 15°C | g/mm <sup>3</sup> | 0.865            |
| Flash Point, COC        | °C                | 211              |
| Viscosity @ 40°C        | cSt               | 50               |
| Viscosity @ 100°C       | cSt               | 8                |
| Viscosity Index         | -                 | 160              |
| Pour Point              | °C                | -40              |

## **SPECIFICATIONS**

GM DEXRON II MAN 339 TYPE D

MB 236.6 CATERPILLAR TO-2

## **TYPES OF PACKING**

Containers of: 1, 5, 208 L

## SAFETY AND HANDLING

This lubricant is made of highly refined base oil and different types of additives. It does not constitute a special hazard or any toxic effects when used properly. Avoid contact with the skin. Prevent any splashing and keep away from combustible materials. Store properly under cover. Dispose off the used oil correctly.