

ETA GREASE

ETA Grease is a premium quality, extreme pressure and multi-functional lithium-soap grease. It is designed for lubrication of various industrial and automotive parts operating under high temperature and extreme pressure conditions.

PRODUCT FEATURES

- * ETA EP grease is a soft grease, specially amplified with high pressure additives for the lubrication of various applications where the conditions are wet and severe.
- * It is formulated to provide extra wear protection under high temperature and loading conditions.
- * It is durable and water resistant. It has excellent oxidation stability.
- * It contains anti-rust, anti-wear, anti-corrosion and anti-oxidant additives.
- * It has superior mechanical stability and has excellent adhesion thus minimizing leakage.
- * Its cream color allows for quick detection of contaminants.

APPLICATION

ETA EP grease is formulated for the lubrication of various applications under severe conditions. It is designed for the lubrications of universal joints, chassis, gearboxes, heavily loaded anti-friction plain bearings, slide-ball and roller-bearings (wheel bearings), and various applications in transport, agriculture, marine, construction, and mining.

TECHNICAL SPECIFICATION

Characteristics	Units	Lithium Base
Color	-	Cream
Thickener	-	Lithium Soap
Extreme Pressure	-	Yes
NLGI Grade	-	2
Dropping Point	°C	185
Base oil Viscosity @ 40°C	cSt	100
Base Oil Viscosity @ 100°C	cSt	9.7
Water Solubility	-	Insoluble
Worked Penetration @25°C	mm/10	280
Operating Temperature Range	°C	-30 to +130

SPECIFICATIONS

ISO 6743-9: L-XBCHB 2
DIN 51 502: KP2K-20

EP NLGI 2

TYPES OF PACKING

Containers of: 0.5, 1, 15, 180Kg

SAFETY AND HANDLING

This lubricant is made of highly refined base oil and different types of additives. It does not constitute a special hazard or any toxic effects when used properly. Avoid contact with the skin. Prevent any splashing and keep away from combustible materials. Store properly under cover. Dispose off the used oil correctly.